MATERIAL SAFETY DATA SHEET

Preparation date: 2014-04-09



SPITFIRE SC Power Cleaner

	0		
HMIS NFPA			Personal protective equipment
Health	3	3	
Flammability	0	0	
Physical Hazard / Instability	0	0	

Version Number: 3

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

MSDS #: Product Code: Recommended use: SPITFIRE SC Power Cleaner

MS0300502

5273489, 5273497, 5273518, 5273526 • Heavy Duty Cleaner and Degreaser

• This product is intended to be diluted prior to use

Manufacturer, importer, supplier:

US Headquarters Diversey, Inc. 8310 16th St. Sturtevant, Wisconsin 53177-1964 Phone: 1-888-352-2249 MSDS Internet Address: www.diversey.com **Emergency telephone number:** Canadian Headquarters Diversey, Inc. - Canada 2401 Bristol Circle Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW	
DANGER. CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED. MAY BE HARMFUL IF SWALLOWED).

Eye contact:CSkin contact:CInhalation:M	Eye contact. Skin contact. Inhalation. Corrosive. Causes permanent eye damage, including blindness. Corrosive. Causes permanent damage. May cause irritation and corrosive effects to nose, throat and respiratory tract. May be irritating to mouth, throat and stomach.
---	---

1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient(s)	CAS #	Weight %	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
2-butoxyethanol	111-76-2	10 - 20%	1400	=220 mg/kg	=450 ppm (4 h)
Alcohol ethoxylates	68439-46-3	10 - 20%	1400	Not available	Not available
Monoethanolamine	141-43-5	5 - 10%	1515	=1 mL/kg	Not available
Benzyl alcohol	100-51-6	5 - 10%	1230	=2 g/kg	=8.8 mg/L (4 h)
Lauryl dimethyl amine oxide	1643-20-5	1 - 5%	2700	Not available	Not available

4. FIRST AID MEASURES

Eye contact:

Skin contact: Inhalation: Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical attention immediately.

Immediately flush with plenty of water for 15-20 minutes. Get medical attention immediately. If breathing is affected, remove to fresh air. Get medical attention immediately.

SPITFIRE SC Power Cleaner

Ingestion:

Aggravated Medical Conditions:

THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If swallowed, give a cupful of water or milk. Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:	The product is not flammable. Extinguish fire using agent suitable for surrounding fire.
Extinguishing media which must not be	used for safety reasons: No information available.
Specific hazards:	Not applicable.
Unusual hazards:	Corrosive material (See sections 8 and 10).

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Use personal protective equipment.
Environmental precautions	Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in
and clean-up methods:	a chemical waste container. Use a water rinse for final clean-up.
Environmental precautions	Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment Eye protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program **Respiratory protection:** that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. Handle in accordance with good industrial hygiene and safety practice.

Hygiene measures:

Ingredient(s)	CAS #	ACGIH	OSHA	Mexico
2-butoxyethanol	111-76-2	20 ppm (TWA)	Skin 50 ppm (TWA) 240 mg/m³ (TWA)	75 ppm (STEL) 360 mg/m ³ (STEL) 26 ppm (TWA) 120 mg/m ³ (TWA)
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m³ (TWA)	6 ppm (STEL) 15 mg/m ³ (STEL) 3 ppm (TWA) 8 mg/m ³ (TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid Appearance: Liquid Aqueous solution Specific gravity: 1.026 Vapor density: No information available Boiling point/range: Not determined Decomposition temperature: Not determined Solubility: Completely Soluble Solubility in other solvents: No information available Partition coefficient (n-octanol/water): No information available Elemental Phosphorus: 0.00 % by wt. **pH:** 12.5 Explosion limits: - upper: Not determined - lower: Not determined Bulk density: No information available Evaporation Rate: No information available Color: Clear, Red Odor: Pine Fresh Melting point/range: Not determined Autoignition temperature: No information available Density: 8.56 lbs/gal 1.026 Kg/L Flash point: > 200 °F > 93.3 °C Viscosity: No information available VOC: 19.7 % Dilution pH: 11.45 @ 1:12

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Stability: Polymerization: Hazardous decomposition products: Materials to avoid: Conditions to avoid:	The product is stable Hazardous polymerization does not occur. None reasonably foreseeable. Acids. Strong oxidising agents. Do not mix with any other product or chemical.
	11. TOXICOLOGICAL INFORMATION
Acute toxicity:	Corrosive. Oral LD50 estimated to be between 2000 - 5000 mg/kg. Dermal LD50 estimated to be >
Component Information:	2000 mg/kg. See Section 3.
Chronic toxicity:	None known
Specific effects Carcinogenic effects: Mutagenic effects: Reproductive toxicity: Target organ effects:	• None known None known None known None known

12. ECOLOGICAL INFORMATION

Environmental Information:

No data available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local applicable regulations.

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, only available through Internet Explorer, http://naextranet.diversey.com/dot/, for up to date shipping information.

DOT (Ground) Bill of Lading Description: LTD. QTY.

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
2-butoxyethanol	111-76-2	Х	Х	Х	-
Alcohol ethoxylates	68439-46-3	-	-	-	-
Sodium xylene sulfonate	1300-72-7	-	-	-	-
Monoethanolamine	141-43-5	Х	X	X	-
Benzyl alcohol	100-51-6	Х	-	Х	-

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
2-butoxyethanol	111-76-2	10 - 20%			Х

Ingredient(s)	САА НАР	CAA ODS	CWA Priority Pollutants
2-butoxyethanol	Х		

SARA 311/312 Hazard Categories

Immediate:	х
Delayed:	-
Fire:	-
Reactivity:	-
Sudden Release of Pressure:	-
Canada	

WHMIS hazard class: E Corrosive material.



Ingredient(s)	CAS #	NPRI
2-butoxyethanol	111-76-2	Х

16. OTHER INFORMATION

Not applicable

Reason for revision: Prepared by: Additional advice:

NAPRAC • Contains an added fragrance, see "Odor" heading in section 9 for specific description • This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.