



EXTENSIBLE FLATBACK KRAFT SPLICING TAPE

DESCRIPTION

This tape is made of water resistant Extensible Flatback Kraft paper and coated with a high tack natural rubber adhesive. This tape offers good holding power and low temperature performance.

MAIN QUALITIES

- Water resistant.
- High tensile strength extensible flatback kraft paper.
- Excellent shear and holding power.
- Hand tearable.
- Acid free (PH neutral).

APPLICATION

- Core and paper splicing.
- Packaging tape in moving industry.
- Carpet underlay seaming tape.
- Picture framing tape.

TECHNICAL DATA

Colour	Brown
Backing	Extensible Flatback, treated Kraft paper
Adhesive	Natural rubber, solvent spread
Thickness	6.7 mil
Adhesion to steel	> 50 oz./in.
Tensile strength	54 lb./in.
Elongation	7%
Application temperature	55 °F (12 °C)
Temperature resistance	Up to 194 °F (90 °C) for 60 minutes

STOCK SIZES

- 48mm x 55m -- 24 rolls/case
- 72mm x 55m -- 12 rolls/case
- 96mm x 55m -- 12 rolls/case

HIGH HOLDING POWER

ACID FREE (PH NEUTRAL)



Please note:

Specifications quoted are averages only and may vary within industry tolerances. The final user must assure product suitability for the application and assumes all risks and liabilities.