

# MATERIAL SAFETY DATA SHEET

John Scoggins Company # 488300  
 P.O. Box 1388  
 Sallisaw, OK 74955  
 Emergency Number: 1-800-426-5529

Date Published: 01/05/02

PC# 48831250

PRODUCT NAME: **WAX BASE FLOORSWEEP**

## 1. HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Liquid Petroleum CAS#: 8009-03-8  
 Sawdust

THIS MATERIAL IS NOT KNOWN TO CONTAIN ANY CHEMICAL LISTED AS A CARCINOGEN OR SUSPECTED CARCINOGEN BY OSHA, IARC, OR THE NATIONAL TOXICOLOGY PROGRAM (NTP) AT A CONCENTRATION GREATER THAN 0.1%.

SARA SECTION 313 STATUS: THIS MATERIAL IS NOT KNOWN TO CONTAIN ANY CHEMICALS ON SARA SECTION 313 LIST AT A CONCENTRATION GREATER THAN 1.0% OR ANY CARCINOGENIC CHEMICAL ON THAT LIST AT A CONCENTRATION GREATER THAN 0.1%

OTHER INGREDIENTS: SEVERELY HYDROTREATED PETROLEUM DISTILLATE AND FUNCTIONARY ADDITIVES

## 2. PHYSICAL / CHEMICAL CHARACTERISTICS

BOILING POINT: (760 MM HG F, C):	N/A
SPECIFIC GRAVITY: (H <sub>2</sub> O=1):	Not known
VAPOR PRESSURE: mm Hg (20 C):	Not Known
MELTING POINT: (F, C):	N/A
pH INFORMATION;	N/A
SOLUBILITY IN WATER (% BY VOL.):	Negligible
VAPOR DENSITY: (AIR=1):	Not known
EVAPORATION RATE (n-butyl acetate=1):	N/A
APPEARANCE & ODOR:	Tan Color/Semi-Solid with bland odor
% VOLATILES BY VOLUME:	0

## 3. FIRE AND EXPLOSION DATA

AUTOIGNITION TEMPERATURE (F, C):	N/A
FLASH POINT, OC, C (F):	>100 (>212)
FLASH POINT, CC, C (F):	N/A
FLAMMABLE LIMITS (% VOL):	LEL-1 UEL-N/A
EXTINGUISHING MEDIA:	Water Fog, Foam, dry chemical, CO2
SPECIAL FIRE FIGHTING PROCEDURES:	Use water to cool containers exposed to flames. Do not enter enclosed or a confined work space without proper protective equipment.
UNUSUAL FIRE AND EXPLOSION HAZARD:	Do not use forced stream as this could cause fire to spread. Containers may rupture from internal pressure if confined to fire area.

NFPA RATING  
 FIRE 1

HAZARD RATING  
 0 - LEAST 3 - HIGH

REACTIVITY	0	1 - SLIGHT	4 - EXTREME
HEALTH	0	2 - MODERATE	

**4. REACTIVITY DATA**

STABILITY:	Stable
CONDITIONS TO AVOID:	Sources of ignition: heat, sparks, and open flame
INCOMPATIBILITY:	Isolate from strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS:	Smoke, CO & CO2 under fire conditions
HAZARDOUS POLYMERIZATION:	Cannot occur

**5. HEALTH HAZARD INFORMATION****EXPOSURE LIMITS:**

OIL MIST: 5MG / M3 WITHIN OSHA, PEL/ACGIH TLV, GOVERNMENT REGULATIONS

INHALATION:	Not considered an inhalation hazard.
EYE:	May cause transient eye irritation characterized by pain, tears, swelling, redness and blurred vision.
Skin Contact:	Not considered a skin contact hazard. If skin contact occurs, wash skin with soap and water.
Ingestion:	Do Not induce vomiting. Get medical attention. Never give anything by mouth to an unconscious or convulsing person.

**6. PRECAUTIONS FOR SAFE HANDLING AND USE**

SPILL PROCEDURES: Clean up spill using shovels. Keep from sewers and natural waterways.

VENTILATION: Use local exhaust and general mechanical ventilation

WASTE DISPOSAL: THIS MATERIAL IS BELIEVED TO BE NON-HAZARDOUS, DISPOSAL SHOULD BE IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL LAWS.

STORAGE: STORE AS AN NFPA CLASS III-B

PRECAUTIONARY LABELING: NONE REQUIRED

**7. SPECIAL PROTECTION INFORMATION**

Avoid contact with eyes. Wear safety glasses or goggles as necessary. Wear chemically resistant gloves and other clothing as required to prevent contact.

**Notice**

The supplier disclaims all expressed or implied warranties of fitness or merchantability for a specific use, with respect to the product, or the information provided herein, except for conformation to contracted specifications.

All information appearing herein is based upon data obtained from manufacturer and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.