

Bravo 1500+ UHS Floor Stripper

Version Number: 1 Preparation date: 2014-04-30

1. IDENTIFICATION

Bravo 1500+ UHS Floor Stripper Product name:

Product Code: 95594995 MS0800128 SDS #: Recommended use:

Industrial/Institutional

Floor stripper

• This product is intended to be diluted prior to use Uses other than those identified are not recommended

Manufacturer, importer, supplier: Canadian Headquarters US Headquarters Sealed Air - Canada Sealed Air 3755 Laird Road

8215 Forest Point Blvd. Charlotte, NC 28273-5509 Phone: 1-888-352-2249

Uses advised against:

Emergency telephone number:

SDS Internet Address: www.sds.sealedair.com

Mississauga, Ontario L5L 0B3 Phone: 1-800-668-3131

1-800-851-7145 (U.S.); 1-651-917-6133 (Int'I)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

Skin corrosion/irritation Category 1B Serious eye damage/eye irritation Category 1



Signal Word: Danger.

Precautionary Statements

CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE.

Avoid contact with eyes, skin and clothing. Causes burns/ serious damage to mouth, throat and stomach. Do not breathe vapors. Wash affected areas thoroughly after handling. Wear chemical-splash goggles, chemical-resistant gloves and protective footwear. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Wash contaminated clothing before reuse. Dispose of in accordance with all federal, state and local applicable regulations.

Health hazards not otherwise classified (HHNOC) - Not applicable Physical hazards not otherwise classified (PHNOC) - Not applicable



Classification for the diluted product @ 1:4

Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A



Dilution Signal word: Warning.

Precautionary Statements

CAUSES SKIN AND SERIOUS EYE IRRITATION.

Avoid contact with eyes, skin and clothing. Wash affected areas thoroughly after handling. May cause irritation to mouth, throat and stomach. Wear chemical-splash goggles and chemical-resistant gloves. IF SWALLOWED: Rinse mouth. Drink a cupful of milk or water. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists: Get medical advice or attention. Dispose of in accordance with all federal, state and local applicable regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Classified Ingredients

<u> </u>				
Ingredient(s)	CAS#	Weight %		
Monoethanolamine	141-43-5	10 - 20%		
Benzyl alcohol	100-51-6	5 - 10%		
Sodium xylene sulfonate	1300-72-7	1% - < 3%		
Diethylene glycol butyl ether	112-34-5	1% - < 3%		

^{*}Exact percentages are being withheld as trade secret information

4. FIRST AID MEASURES

Undiluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

Most Important Symptoms/Effects: No information available.

Immediate medical attention and special treatment needed Not applicable.

Aggravated Medical Conditions: Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.

Diluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists: Get medical advice/attention

Skin: IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention

Inhalation: No specific first aid measures are required

Ingestion: IF SWALLOWED: Rinse mouth. Drink a cupful of milk or water.

5. FIRE-FIGHTING MEASURES

Specific methods: No special methods required

Suitable extinguishing media: The product is not flammable. Extinguish fire using agent suitable for surrounding fire.

Specific hazards: Corrosive material (See sections 8 and 10).

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Put on appropriate personal protective equipment (see Section 8.).

Environmental precautions Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in and clean-up methods:

a chemical waste container. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

Aerosol Level (if applicable): Not applicable

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	CAS#	ACGIH	OSHA
Monoethanolamine	141-43-5	6 ppm (STEL)	3 ppm (TWA)
		3 ppm (TWA)	6 mg/m³ (TWA)
Benzyl alcohol	100-51-6	-	-
Sodium xylene sulfonate	1300-72-7	-	-
Diethylene glycol butyl ether	112-34-5	10 ppm (TWA)	-

Undiluted Product:

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Chemical-splash goggles. Eye protection: Hand protection: Chemical-resistant gloves.

Skin and body protection: Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear. Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program

that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever

workplace conditions warrant a respirator's use.

Handle in accordance with good industrial hygiene and safety practice. Hygiene measures:

Diluted Product:

Personal Protective Equipment

Eye protection: Chemical-splash goggles. Hand protection: Chemical-resistant gloves.

Skin and body protection: No personal protective equipment required under normal use conditions. Respiratory protection: No personal protective equipment required under normal use conditions. Handle in accordance with good industrial hygiene and safety practice. Hygiene measures:

9. PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Liquid Color: Clear, Straw Evaporation Rate: No information available Odor: Solvent Solvent

Odor threshold: No information available. Boiling point/range: Not determined

Melting point/range: Not determined Decomposition temperature: Not determined

Autoignition temperature: No information available Solubility: Completely Soluble

Solubility in other solvents: No information available Relative Density (relative to water): 1.016 Density: 8.47 lbs/gal 1.016 Kg/L Vapor density: No information available Bulk density: No information available Vapor pressure: No information available.

Flash point: > 200 °F > 93.3 °C Partition coefficient (n-octanol/water): No information available

Dilution Flash Point: > 200 °F > 93.3 °C Viscosity: No information available

VOC: 11.27 % * Elemental Phosphorus: 0.00 % by wt.

pH: 12.1 VOC % by wt. at use dilution 2.25 % * **Dilution pH:** 11.45 @ 1:4 Flammability (Solid or Gas): Not applicable Metal Corrosion: Not determined

Explosion limits: - upper: Not determined - lower: Not determined

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity: Not Applicable Stability: Not Applicable The product is stable

Hazardous decomposition products: None reasonably foreseeable.

Materials to avoid: Do not mix with any other product or chemical unless specified in the use directions.

Conditions to avoid: No information available.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Eye contact, Skin contact, Inhalation, Ingestion

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: Corrosive. Causes severe burns. Symptoms may include burns, blisters, redness and pain (which may be delayed). **Eye contact:** Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.

Ingestion: Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea. **Inhalation:** May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and

difficulty breathing.

Sensitization: No known effects. Target Organs (SE): None known Target Organs (RE): None known

Numerical measures of toxicity

ATE - Oral (mg/kg): >5000 ATE - Dermal (mg/kg): >5000 ATE - Inhalatory, mists (mg/l): 12 ATE - Inhalatory, vapors (mg/l): >50

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: This product, as sold, if discarded or disposed, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Dispose in compliance with all Federal, state, provincial, and local laws and regulations. This product, when diluted as stated on this SDS, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the waste solution meets RCRA criteria for hazardous waste. Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

Contaminated Packaging: Do not re-use empty containers.
RCRA Hazard Class (undiluted product): Not Regulated
RCRA Hazard Class (diluted product): Not Regulated

14. TRANSPORT INFORMATION

<u>DOT/TDG/IMDG:</u> Proper shipping descriptions can vary by pack size. Please refer to the Diversey HazMat Library, **only available through** Internet Explorer, http://naextranet.diversey.com/dot/, for up to date shipping information.

DOT (Ground) Bill of Lading Description: UN2491, ETHANOLAMINE SOLUTIONS, 8, III

IMDG (Ocean) Bill of Lading Description: UN2491, ETHANOLAMINE SOLUTIONS, 8, III

15. REGULATORY INFORMATION

International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65.

RIGHT TO KNOW (RTK)

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	=	=	=
Monoethanolamine	141-43-5	Х	Х	Х	-
Benzyl alcohol	100-51-6	X	=	X	=
Sodium xylene sulfonate	1300-72-7	-	=	=	-
Diethylene glycol butyl ether	112-34-5	-	Х	-	-

CERCLA/ SARA

Ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Diethylene glycol butyl ether	112-34-5	1% - < 3%			X

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Diethylene glycol butyl ether	X		

SARA 311/312 Hazard Categories

Immediate: X
Delayed: Fire: Reactivity: Sudden Release of Pressure: -

Canadian Regulations

Ingredient(s)	CAS#	NPRI
Diethylene glycol butyl ether	112-34-5	X

16. OTHER INFORMATION

NFPA (National Fire Protection Association)

Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 3 Flammability 0 Instability 0

Version Number: 1

Preparation date: 2014-04-30

Reason for revision: Not applicable Prepared by: NAPRAC

Additional advice: • Does not contain an added fragrance

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.