

Victoria Bay

Quality products for everyday needs.

Floor Sealer



DESCRIPTION

Specially designed to seal porous and worn floor surfaces yielding a smooth base for subsequent application of finish coats. Compatible with all types of acrylic emulsion finishes and effective for use on all types of resilient floors. Special wetting agents allow for the penetration into microscopic pores and ridges of floor surfaces.

Please read entire container label for detailed instructions and safety information.

DIRECTIONS

1



Wear safety glasses & gloves
Usar gafas de seguridad y guantes

2



Strip floor and apply 3 - 7 coats evenly
Limpie el piso y aplique uniformemente 3 - 7 capas

3



Allow to dry 30 - 45 minutes between coats
Deje secar 30 - 45 minutos entre una capa y otra

4



Completely dry between coats and allow 24 hours before use
Seque completamente entre una capa y otra, y deje pasar 24 horas antes del uso

5



Do not apply more than 4 coats in a 24-hour period
No aplique más de 4 capas en un período de 24 horas

FEATURES

- Semi-permanent
- Acrylic cross-link
- Low viscosity formula

ADVANTAGES

- May be stripped
- Suitable for use under all acrylic finishes
- Large coverage area per gallon

BENEFITS

- Provides versatility in floor care
- Eliminates duplicate products in inventory
- Economical

SPECIFICATIONS

Color	White
Fragrance	Characteristic
pH Range	8.5-9.0
Dilution	RTU
Density	8.50
Non-Volatile Solids	18%
Coverage	2000 sq ft/gal

REORDER

D00044	4/1 gallon
D00045	5 gallon
D20363	2/2.5 gallon

victoriabayproducts.com | 255 Route 1 & 9, Jersey City, NJ 07306 | (800) 535-5053

Guarantee: We guarantee your complete satisfaction with this product's performance. If dissatisfied for any reason, return any unused portion for credit within one year of the date of manufacture.