



iShine™

high solids floor finish

Spartan's most popular finish year after year, iShine is 25% high solids with patented optically enhanced polymer technology that amplifies the overall gloss and clarity of your floors. The unique blend possesses cutting edge raw materials to form a high solids finish that provides total protection in just four coats.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee, OH 43537
 1-800-537-8990
 www.spartanchemical.com

EXCELLENT GLOSS AND CLARITY:

In a 31-day test of iShine and a competitive product, iShine out-performed the competition in overall gloss, wear resistance, and gloss retention. With a higher than average gloss build and better than average gloss retention, iShine is proven effective over the competitions' performance.

NON-YELLOWING, TRUE COLOR ENHANCEMENT:

iShine reflects the true coloration of flooring, dries crystal clear and will not discolor or cast any yellowing tones to the floor. The actual color of the floor covering shines through while optical enhancers perfect blemishes.

PROTECTION PERFORMANCE:

iShine is a durable finish that has excellent scuffmark, water spot, black heel mark and powder resistance. The 25% solids floor finish is formulated to provide maximum protection.

SAVE ON LABOR COSTS – QUICK BUILDING:

Since only four coats of finish are needed with iShine to provide superior protection, labor costs are minimized. Unlike most high solids finishes, the technology found in iShine creates great ease of application and incredible leveling. iShine's high solid formula builds quickly offering more protection in each coat.

UL APPROVED:

Independent testing for slip resistance by Underwriter Laboratories confirms the static coefficient of friction of iShine meets or exceeds 0.5 as determined by ASTM Method D 2047.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

INITIAL APPLICATION:

1. Completely strip all old wax or floor finish. Depending upon build-up, use warm or room temperature water (80°F - 120°F) and a Spartan stripper.
2. Remove all stripping solution and follow with two to three clear water rinses.
3. When flooring is old, abused or damaged, two coats of a Spartan sealer is recommended, although iShine may be used as a self-sealing finish.
4. Apply iShine in a uniform coat. Let dry thoroughly for 30 to 40 minutes until surface is dry to the touch. Apply subsequent coats in the same manner. Two to four coats are recommended.

MAINTENANCE:

Routine: Dust mop with Spartan's Dust Mop/Dust Cloth Treatment™ and damp mop with a Spartan neutral cleaner.

Weekly: Dust floor with Spartan's Dust Mop/Dust Cloth Treatment and damp mop with a Spartan neutral cleaner. To repair traffic areas between finish applications, use Spartan Bounce Back®, Spraybuff or SunSwept®. Be careful to follow the directions for use. (Traffic lanes may be recoated as necessary.)

Periodically: Dust mop floor and scrub. Reapply iShine as needed.

Yearly: Deep scrub and recoat; or completely strip, reseal if necessary and reapply iShine.

NOTE: For best results always use Spartan floor cleaners and strippers.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Total Solids – 34.5%
 Non-Volatile Solids – 25%
 pH (Concentrate) – 8.0 – 9.0

Stability:

- a. Storage @24°C/75°F – One year minimum
- b. Accelerated @49°C/120°F – 30 days minimum
- c. Freeze/Thaw – Can withstand three cycles

Gloss (Gardner)

- a. 1 coat – 90
- b. 2 coats – 93

COVERAGE:

Up to 3,000 square feet per gallon depending on application method and porosity of floor.

PACKAGING	
405560	275-gallon totes
405555	55-gallon drum
405530	30-gallon drum
405515	15-gallon drum
405505	5-gallon pail
405504	1-gallon (4 per case)



Label copy is provided in English, Spanish, and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Distributed by:



Product Available Worldwide. For institutional and industrial use only.

© SCC 3/11 L4055