


Victoria Bay

Quality products for everyday needs.

Urethane High Speed Floor Finish & Sealer



DESCRIPTION

This product is designed for heavy traffic areas such as supermarkets, retail, and institutional settings on all types of resilient flooring. Unique water based urethane emulsion gives a superior wet look gloss with superb detergent resistance and durability. Contains UFW technology to prevent discoloration and dirt penetration to stay looking clean longer, extending the period between stripping cycles.

Note: It is always recommended to wait 24 hours before burnishing; however, Urethane High Speed Floor Finish & Sealer can be burnished 2 hours after product dries.

Please read entire container label for detailed instructions and safety information.

DIRECTIONS

1



Wear safety glasses & gloves

Usar gafas de seguridad y guantes

2



Strip floor and apply 3 - 7 coats evenly

Limpie el piso y aplique uniformemente 3 - 7 capas

3



Allow to dry 30 - 45 minutes between coats

Deje secar 30 - 45 minutos entre una capa y otra

4



Completely dry between coats and allow 24 hours before use

Seque completamente entre una capa y otra, y deje pasar 24 horas antes del uso

5



Do not apply more than 4 coats in a 24-hour period

No aplique más de 4 capas en un período de 24 horas

FEATURES

- High solids
- 'Crystal Clear' film
- Urethane fortified
- Fast Cote technology

ADVANTAGES

- Requires fewer coats
- Never yellows
- Extremely durable
- Goes down smooth and easy

BENEFITS

- Saves time and labor
- Longest lasting appearance
- Holds up under heavy traffic
- Fast drying

SPECIFICATIONS

Color White
Fragrance Characteristic
pH Range 7.5-8.0
Dilution RTU
Density 8.60
Non-volatile solids 22%
Coverage 2000 sq ft/gal

REORDER

D00047 5 gallon

D20368 2/2.5 gallon

victoriabayproducts.com | 255 Route 1 & 9, Jersey City, NJ 07306 | (800) 535-5053

Guarantee: We guarantee your complete satisfaction with this product's performance. If dissatisfied for any reason, return any unused portion for credit within one year of the date of manufacture.