

Premia[®] Ultra High Speed Floor Finish



Ultra High Speed floor finish that offers great performance and "wet look" appearance with low maintenance requirements.

Excellent Performance

- "Wet look" gloss
- Great burnish response that "pops" with propane, battery or electric equipment
- Superior resistance to dirt embedment, scratching, scuffing and marking

Easy-to-Use

- Easy to apply using standard mop or applicator
- Enables flexibility in maintenance procedures and burnishing frequency while still maintaining a great appearance

Designed with Environment in Mind

- New formula contains lower VOCs and is low odor
- Contains no fluorochemicals
- Contains readily biodegradable surfactants

Designed For

- Healthcare
- Education
- Retail
- BSC
- Government

Use Overview

Premia® Ultra High Speed Floor Finish is a labor-saving floor finish that delivers "wet look" gloss without daily burnishing. It can be used on all types of resilient floors. Non-resilient floors should be sealed first.

- Clean floor.
- Strip floor if necessary. Apply 2–4 coats of Premia® Ultra High Speed Floor Finish using a clean mop, the Diversey ProSpeed^{TM/MC} or TrailBlazer^{TM/MC} Floor Finish Applicator System allowing 30 minutes drying time between coats. Apply additional coats if a higher gloss is desired.
- Floors will be very slippery until dry. Meets ASTM D2047 requirement for slip resistance.

Burnishing

Dust mop or sweep floor. Clean floors with any cleaner.

Opaque white liquid

0.5 minimum (ASTM D2047)

>200° F (>93.4° C)

8.4

Ammonia

Dispersible

2 years

20

1.03

- Use autoscrubber with red pad.
- Burnish floor using light color UHS synthetic burnishing pad (not recommended to use natural Hog hair pad). Suitable to be burnished with cord electric, battery or propane burnishers 1500 rpm and up.
- Dust mop floor.

Description Color/Form

Flash Point

pН

Scent

Shelf Life

Solids %

Solubility

Slip Resistance

Product Specifications

Avai	lab	le	lte	ms

Product Code	Description/Package Size	Dilution
5039393	4 x 1 gallon / 3.78 L Containers	Ready-To-Use
5039422	1×5 gallon / 18.9 L Envirobox ^{TM/MC} (TrailBlazer ^{TM/MC} ready)	Ready-To-Use
5549351	6 x 2.5 L / 2.64 Qt. ProSpeed ^{™/MC} BIB (Bag-in-Box)	Ready-To-Use

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at www.diversey.com or by calling 888 352 2249.

Hazard Rating

Specific Gravity

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.





Deep Scrub/Top Scrub and Recoating

- Dust mop or sweep floor.
- Scrub floor using UHS Cleaner. Use blue scrubbing pad and dilute product 1:512.
- Apply 1–2 coats of Premia[®] Ultra High Speed Floor Finish.

Stripping

- Strip floor using Pro Strip[®] or Freedom[®].
- Dilute product according to label use instructions.