

SUPER KEMITE®



Heavy Duty Cleaner • Degreaser

Designed for tough jobs, this product takes over where all purpose cleaners leave off. Formulated to instantly dissolve and emulsify heavy grease, carbon deposits, rubber burns, oil, ink and dirt accumulations, just spray or mop on and rinse it off. This products low sudsing properties make it perfect for use in automatic scrubbers and pressure washers. So versatile that dilutions for this product range from 4 ounces per gallon of water (1:32) for light duty cleaning to 26 ounces per gallon (1:5) for extreme situations. Nonflammable, this product also works well in hard or soft water.

Uses

- Campers
- Concrete surfaces
- Construction vehicles
- Counter tops
- Factories
- Floors
- Garages
- Kitchen
- MachineryOffices
- Recreational vehicles
- Restaurants
- Schools
- Walls

Benefits

- Heavy duty cleaning made easy with this advanced grease cutting formula. An effective blend of wetting agents, detergents and water-based solvent provide optimum cleaning power.
- Versatile May be used in a variety of cleaning applications with different dilutions. Concentrated for greater economy, this industrial cleaner is low sudsing and may be used in automatic scrubbers.
- Fast penetration and breakdown of tough greases and oils.
 Works great on animal fats as well as petroleum based soils.

Properties

Color	ExcellentExcellent
Flash point	None
Foaming	
Fragrance	Cherry
Fumes	None
Hq	13.0 - 13.9
Rinsability	Very Good
Solubility in water	Complete
Specific gravity	1.06
Viscosity	10 centipoise
Wetting	Very good
Shelf life	

Authorized Betco Distributor

Directions For Use

Read the entire label before using this product.

For cleaning concrete, floors, walls, machinery, engines and a variety of other water washable surfaces soiled with grease or oil. *Not recommended for use on glass or water based paint. Concentrated product will discolor aluminum and other soft metals.* FLOORS, WALLS, GENERAL MAINTENANCE: LIGHT SOIL: Dilute 4 oz./gal. or 31 mL/L (1:32) with water. MEDIUM SOIL: Dilute 13 oz./gal. or 100 mL/L (1:10) with water. HEAVY SOIL: Dilute 26 oz./gal. or 200 mL/L (1:5) with water. KITCHENS, ENGINES, MACHINERY, CONCRETE, SWIMMING POOLS, SHOWERS, WHITE WALL TIRES: Dilute 13 oz./gal. or 100 mL/L (1:10) with water. NEVER LESS THAN: Dilute 13 oz./gal. or 100 mL/L (1:10) with water.

Safety

Keep out of reach of children. For institutional and commercial use. DANGER: Corrosive. Causes Burns. Vapors harmful. Contains Sodium Metasilicate and 2-Butoxyethanol. Avoid contact with skin and eyes. Wear chemical anti-splash goggles and suitable gloves and boots. Harmful if swallowed. FIRST AID: Remove contaminated clothing immediately. Skin and Eyes: Flush skin and eyes immediately with large quantities of water for at least 15 minutes. Seek immediate medical attention. Ingestion: If swallowed, contact a poison control center immediately for treatment advice. Have conscious person take sips of water if able to swallow. Never give anything by mouth to an unconscious person. Do not induce vomiting unless instructed to do so by poison control center or doctor. Inhalation: Remove to fresh air. If not breathing, call 911 or ambulance, then administer artificial respiration, preferably mouth-to-mouth.

Acceptance

Acceptable for use in federally inspected meat and poultry plants. Previous classification +A-4 for use as a floor and wall cleaner.

Available In

Case/4 - 1 Gallon (3.78 L):Item #10304-00 Case/5 Gallon (18.9 L): Item #10305-00 Drum/55 Gallon (208 L): Item #10355-00 Disposable Tote/275 Gallon (1041 L): Item #10327-00 Reusable Tote/330 Gallon (1249 L): Item #10333-00

Literature Item #10392-92

C7030 - Industrial - Butyl Based Degrease

05.05

