JohnsonDiversey



LinoBASE® Linoleum Sealer

A specially formulated sealer for linoleum floors

Versatile

- Forms a very tough, non-removable sealer that helps keep linoleum floors looking good for many years
- Brings back the true color even on old, worn and faded linoleum. In addition, it prolongs the life of linoleum floor

Durable

- Sealer will not powder or crack even when applied on very porous linoleum
- This new and unique polymer system creates a tough seal with superior penetration, adhesion and cohesion properties, giving it a much higher resistance to abrasion and chemicals than conventional sealers
- Protects against water damage and against conventional alkaline floor cleaners

Designed For

RETAIL EDUCATION GOVERNMENT







JohnsonDiversey

Use Overview:

LinoBASE^{*} **Linoleum Sealer** is specially formulated to form a long lasting seal over the linoleum floor and helps prevent it from being stained or damaged by water, conventional alkaline cleaners or strippers.

- Blockade area to be stripped or sealed.
- Floors can become very slippery when stripper is applied, exercise caution.
- Remove all old finish using LinoSAFE[®] Linoleum Stripper according to label directions.
- If there is no finish on the linoleum, clean with Stride[®] Neutral Cleaner at recommended dilution or with LinoSAFE[®] Linoleum Stripper at 2 oz. per gallon for removal of heavier soils.
- Rinse and allow to dry.
- Damaged linoleum should be made uniform in texture and appearance before application of LinoBASE[®] Linoleum Sealer.
- Dry-buff damaged linoleum with a #000 steel wool pad on a 175 rpm machine.
- Wipe away residual dust with a dust mop and allow to dry.
- Apply 2 uniform coats of LinoBASE[®] Linoleum Sealer using a clean rayon blend mop.

Product Specifications:

John	sonDiverse			all later
ារា	IOBAS	Re	The second second	
	POUR LE LIN		a series and a series of the s	
1591/5US Gal	CONVER	5104888	and the spectrum	

- Allow 45–60 minutes drying time between coats depending on temperature and humidity.
- Topcoat with any JohnsonDiversey floor finish according to label directions.

Note: **Carefree**[®] **Matte Low Gloss Floor Finish** is the preferred finish for linoleum floors.

Boiling/Condensation Point	> 212° F (> 100° C)	Scent	Mild
Color/Form	Opague white liquid	Shelf Life	2 years
Melting/Freezing Point	32° F (0° C)	Slip Resistance	Meets ASTM D2047 requirements
Non-volatile Solids	15%	Solubility in Water	Complete
рН	7.7	Specific Gravity	1.03

Available items:

PRODUCT CODE	DESCRIPTION/PACKAGE SIZE	DILUTION
5104888	1 x 5 gallon / 18.9 L Envirobox ^{TM/MC}	Ready-To-Use

Hazard Rating:

HMIS	Concentrate	NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

Safety Reminder:

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDSs are available on-line at www.johnsondiversey.com or by calling 1-888-352-2249.

For additional information, please visit: www.johnsondiversey.com