

# **High Noon**<sup>TM/MC</sup> Urethane Fortified UHS Floor Finish



## A high solids UHS floor finish for floors that demand excellent gloss and durability.

#### **Excellent Performance**

- Built with tough all-acrylic polymers and fortified with urethane for unmatched durability
- Reduces labor costs by extending recoat and strip-out cycles

#### **Excellent Appearance**

- Burnishes to a rich deep gloss
- Retains good looks longer between burnishings
- Maintains clarity and color better than finishes that contain styrenated polymers

#### **Designed For**

- Health Care
- Education
- Retail
- Government
- BSC

### **Use Overview**

**High Noon**<sup>TMMC</sup> **Urethane Fortified UHS Floor Finish** gives you high-gloss brilliance and durability in fewer coats, saving you time and labor.

#### **Preparation**

- Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- > Strip floor using any Diversey stripper per the instructions on the stripper label.

#### Coating

- Apply 3 or more medium coats of High Noon<sup>TMMC</sup> Urethane Fortified UHS Floor Finish using a clean mop or the Diversey ProSpeed<sup>TMMC</sup> Floor Finish Applicator System. Apply additional coats until desired gloss is obtained. On porous resilient or stone floors, seal first with 2 coats of recommended Diversey sealer.
- Allow 30–45 minutes of drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before burnishing.

#### **Maintenance**

- Dust mop or sweep. Clean the floor daily with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to label directions.
- > To enhance appearance, burnish using the appropriate pads.
- Clean and restore gloss with recommended Diversey cleaner. Apply using an autoscrubber or damp mop, let floor dry and then burnish.

#### Recoating

Description

Color/Form

pН

Scent

Shelf Life

Specific

Gravity

- Dust mop or sweep.
- Clean the floor with a mop or an automatic scrubber suing the recommended Diversey cleaner according to label directions.
- Blockade area and apply 1–2 uniform coats of finish using a clean finish mop.
- Allow finish to cure for 24 hours before burnishing.

Opaque white, liquid

Concentrate

Characteristic

8.5

2 years

1.031

#### **Product Specifications**

#### **Available Items**

Product Code	Description/Package Size	Dilution
5104829	1 x 5 gallon / 18.9 L Envirobox <sup>™MC</sup>	Ready-To-Use
4972051	6 x 2.5 L / 2.64 Qt. ProSpeed <sup>TMANC</sup> BIB (Bag-in-Box)	Ready-To-Use
4003110	4 x 1 gallon / 3.78 L Containers	Ready-To-Use

#### **Safety Reminder**

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at www.diversey.com or by calling 888 352 2249.

#### **Hazard Rating**

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.



