

*Carefree*

# Floor Sealer/Finish

*This easy-to-apply floor sealer/finish is formulated to work with any maintenance method and equipment on all types of floors. Replace all your floor finishes with one!*

#### **Ultra Compatible Formulation™**

CAREFREE® works on nearly all types of floors and responds beautifully to conventional, high-speed or UHS equipment and maintenance procedures.

#### **Works In Non-Buff, Dry Buff And Spray Buff Programs**

Responds to 175 through 2000 equipment.

#### **Long Lasting Performance**

A sealer and finish... easy on, easy off... exceptional clarity, high gloss and excellent durability.



**Johnson wax**  
**PROFESSIONAL**

# CAREFREE™ SEALER/FINISH

## Profile

<b>WHAT IS IT?</b>	A sealer/ finish that works on nearly all types of floors and responds beautifully to conventional, high-speed or UHS equipment and maintenance procedures.
<b>WHAT DO I USE IT ON?</b>	Designed for use on any resilient floors and non-resilient floors, including vinyl, vinyl composition, vinyl asbestos, asphalt tile, rubber, terrazzo, slate brick, unglazed ceramic or quarry tile, honed marble and honed granite. Test on concrete, highly polished marble and granite for adhesion
<b>How do I USE IT?</b>	<p><b>Applying Floor Finish:</b> <b>1.</b> Strip floor using Johnson Wax Professional stripper according to directions. <b>2.</b> Apply 2-4 coats of finish using a clean mop. Apply additional coats if a higher gloss is desired. <b>3.</b> Allow 30 minutes drying time between coats.</p> <p><b>Maintenance:</b> <b>1.</b> Dust mop or sweep. <b>2.</b> Clean floor with Johnson Wax Professional cleaner following label directions. <b>3.</b> To enhance gloss, spray buff using recommended Johnson Wax Professional spray maintainer or with red pad and 175 - 1500 rpm equipment. Dry buff using a white pad and 1000 - 1500 rpm equipment. UHS burnish with a medium to aggressive pad and 2000+ rpm equipment.</p> <p><b>Before Recoating:</b> <b>1.</b> Dust mop or sweep. <b>2.</b> Deep scrub floor using Johnson Wax Professional cleaner according to label directions. <b>3.</b> Apply 1 or 2 coats using a clean mop.</p>
<b>FOR BEST RESULTS:</b>	<b>1.</b> Do not dilute. <b>2.</b> Do not use on surfaces colder than 10°C (50°F). <b>3.</b> To avoid contamination, do not return unused finish to original container. <b>4.</b> Not intended for use on wood.
<b>NOTE:</b>	Floors can be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.

## Specifications

<b>Dilution:</b> . . . . .	Ready-to-use
<b>Non-volatile Solids:</b> . . . . .	20.0%
<b>Drying Time:</b> . . . . .	<b>Recoat:</b> 30 minutes (under normal conditions) <b>Traffic:</b> 30 minutes or less (under normal conditions)
<b>Shelf Life:</b> . . . . .	2 years
<b>Slip Resistance:</b> . . . . .	0.5 minimum (ASTM D2047)
<b>HMIS Hazard Ratings:</b>	
Health . . . . .	1
Flammability . . . . .	0
Reactivity . . . . .	0

## Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS's are available on-line at [www.johnsondiversey.com](http://www.johnsondiversey.com) or by calling 1-888-352-2249.

## Packaging

PACK / SIZE	PRODUCT CODE
4 / 1 Gallon (3.78 L) containers	5432
1 / 5 Gallon (18.9 L) Envirobox	5431



**Johnson wax**  
**PROFESSIONAL**

FOR COMMERCIAL & INDUSTRIAL USE ONLY

© 2003 JohnsonDiversey, Inc., Sturtevant, WI 53177-0902. All Rights Reserved.

For further information on special applications or other Johnson Wax Professional products, contact your JohnsonDiversey representative, or call us at 1-800-558-2332 or visit our web-site at [www.johnsondiversey.com](http://www.johnsondiversey.com)