

# TERAND

The Maintenance Professional's Choice

## PENETRANT LUBRICANT DEMOISTURANT PROTECTANT 209

Non-flammable, all purpose, non-conductive mechanic's spray. Penetrates through rust and corrosion to loosen frozen nuts and bolts. Displaces moisture in wet electrical systems. Leaves treated surfaces protected with residual anti-corrosive film. Does not contain any chlorinated solvents. Safe around most plastic and paint. Includes extension tubes for easier application to remote areas.



### FEATURES

- All-Purpose Mechanic's Spray
- Non-Chlorinated
- Non-Flammable
- 39 kV Dielectric Strength
- Frees Frozen Parts
- Dries Out Wet Electrical Equipment
- Leaves Protecting, Waterproof Film
- Inhibits Corrosion

### FOR USE BY

Auto Mechanics, Utility Companies, Marine Repair, Industrial Plants, Refineries, Food & Bottling Plants, Heavy Equipment Companies, Railroads, Trucking, Mining Operations, Oil Fields, Motors, Frozen Nuts & Bolts, Hinges, Screws, Clamps, Linkages, Fasteners, Molds, Lug Nuts, Threaded Parts, Tools, Engine Parts, Motors, Bearings, Gear, Relays, Starters, Generators



### Specs:

Can Size	16 oz.
Net Weight	11 oz.
Shipping Weight	13 lbs.
Packaged	12 cans per case
Extender Tube	Yes
<b>Regulatory:</b>	
Ozone Depleting Compounds	None
Recyclable Package	Yes
VOC%	3.34%
VOC Restricted Area(s)	None
NFPA Code 30B Storage Rating	Level 2 Aerosol
DOT Proper Shipping Name	Limited Quantity, LTD QTY
<b>Physical Characteristics:</b>	
Appearance	Brown Liquid
Odor	Solvent Odor
Spray Pattern	Triangular
Specific Gravity	0.84
Flammability	Non-Flammable Spray
Dielectric Strength	39 kV
Propellant	Carbon Dioxide
Solvent System	Aliphatic

www.cpaeroscience.com  
(800) 327-1835

