

TECHNICAL INFORMATION

- Feature** : Crepe paper coated with synthetic rubber adhesive (Hot Melt)
- Product** : 800
- Application** : Designed for use as general purpose masking tape, ideal for paint work applications or stoving operations until 140°F (60°C) / 1 hour, protection, color separation, holding. Also recommended to temporary attach inspection stickers, nameplates, instructions and work orders during manufacturing and assembly operations.
- Color** : Natural
- Physical Properties** :

Total thickness (mils) PSTC-133	Tensile strength (lbs / inch) PSTC-131	Elongation at break (%) PSTC-131	Adhesion to steel (oz / inch) PSTC - 101	Holding Power 1" X 1/2" (minute) PSTC-107
4.65 ± 8%	20 ± 2	less than 20	>45	Min 3000

TEST CONDITION

- Temperature : 73°F (23°C) ± 1°C
- Relative Humidity : 50% ± 5%

Storage and usage condition:

Masking tape should be stored in its original packaging in a cool, dry area away from direct sunlight. Should be used within 6 months of date of shipment. Surface to which masking tape is applied should be clean dry and free of dust, oil or grease and other contaminants.

Note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The physical and performance characteristics shown are average obtained from test recommended by PSTC or our procedures and the user must by test or otherwise.