



# Brand 3200 TopLine Speed Burnish Pad

## 1.0 Product Description

This product is a floor maintenance burnishing pad for use on ultra high speed floor machines that operate in the range of 1500 - 3000 rpm. The pad is made of high quality synthetic fibers in a non-woven web bonded with a durable resin system that permeates the entire pad. The pad is nominally one inch thick and is made in various sizes.

## 2.0 Intended Use

The pad is used on cord electric, battery electric or propane powered floor machines for burnishing a wide variety of floor finishes. The pad may be used for dry buffing, moderate spray cleaning or as part of the TopLine System. The system includes cleaning and conditioning the floor surface with TopLine Conditioner and the TopLine Pre-Burnish Pad.

## 3.0 Standard Sizes

Circular discs:

Diameter (Inches)	Center Hole (Inches)
13 - 27 in one inch increments	3 3/8
20, 22 and 27	1/4

Other sizes available upon request

## 4.0 Colors

White/Amber

## 5.0 Requirements

### General Requirements

This product shall be made of synthetic fibers and adhesives and shall not be significantly affected by water, detergents and cleaners normally used for floor maintenance. The product shall be reversible and nominally one inch thick.

## 5.0 Requirements (Continued)

Typical Properties:		
Property	Value	Test Method
O.D. Dimension	Designated size ± 1/16 inch	SB-61
Thickness	1 inch nominal	SB-66
Weight (4 in. x 6 in.)	18.6 g	
Fiber type	Proprietary synthetic mixture of sizes	
Average tensile strength	88 lbs./2 in.	
Alkali Resistance (Tensile Retention)	80%	
Wear (weight loss)	34%	SB 2.0
Recycle content of packaging	Not less than 35% post-consumer recycled material	

## 6.0 Packaging and Marking

**Packaging:** Circular pads:  
13 inch through 24 inch - 5 pads per case  
25 inch through 27 inch - 2 pads per case

**Marking:** Each carton shall be labeled to identify the contents by product name, size and manufacturer.

## 7.0 Pad Use and Cleaning

### Directions for Use:

TopLine system

1. Dust mop
2. Clean and condition floor by mop applying the TopLine Conditioner or scrubbing with an automatic or rotary machine.
3. Burnish floor to a high gloss with the TopLine Speed Burnish Pad.

### Pad Cleaning:

Pads may be hosed out using a pressure spray nozzle to remove soil. Pads may be soaked in detergent or diluted stripping solution to dissolve caked on soil or finish prior to cleaning.



**3M™ Brand 3200 TopLine Speed Burnish Pad (continued)**

---

**3M Branch Sales Offices**

**ANCHORAGE**

11151 Calaska Circle  
Anchorage, AK 99515  
Area Code 907 Tel. 522-5200  
Facsimile 907-522-1645

**CONTINENTAL UNITED STATES**

Customer Service Department  
3M Center Building 223-3E-04  
St. Paul, MN 55144-1000  
Order Entry 1-800-698-4595  
Facsimile 1-800-447-0408

**HONOLULU**

4443 Malaai Street  
Honolulu, HI 96818  
Mail to: P.O. Box 30048  
Honolulu, HI 96820  
Area Code 808 Tel. 422-2721  
Facsimile 808-422-9557

**3M CANADA**

1840 Oxford Street East  
London, Ontario, Canada  
N5V 3G2  
Mail to: P. O. Box 5757  
London, Ontario, Canada  
N6A 4T1  
519-451-2500  
Fax: 519-452-6262

"3M" is a trademark of 3M.

**Important Notice:**

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors, 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.

---

**3M Commercial Care Division**

