



PHOTON MAX™

with **SRT™**
SCUFF RESISTANT TECHNOLOGY



High Gloss Remarkable Response Floor Finish

Betco's Photon Max™ with Scuff Resistant Technology™ (SRT) is a highly repairable, low odor, black heel mark resistant floor finish. Designed for Ultra High Speed routine maintenance programs in high profile, high traffic areas, Photon Max with SRT provides a dramatic gloss response when burnished. This self-sealing, brilliant, high gloss, extended wear formula retains film integrity and outstanding gloss and black heel mark resistance even after repeated detergent cleaning. Superior soil resistance and film clarity helps extend top scrub and recoat intervals as well as stripping cycles. Its excellent leveling and low odor makes it easy to apply.

Uses

- Resilient Tile
- Terrazzo
- Linoleum

Features

- Superior Black Heel Mark Resistance
- Easy to apply and maintain superior gloss
- Exceptional response to propane, battery or electric equipment
- Excellent "Off the Mop" gloss
- Superior soil resistance
- Extremely low odor

Properties

Color (dried film)	Crystal clear
Color (liquid)	White
Coverage.....	2000 - 3000 sq. ft./gallon
Dry time.....	20 - 30 minutes
Fragrance.....	Mild
Freeze/thaw stability	3 cycles
Gloss (ASTM D1455-87).....	One coat 85 - 90 Two coats 97 - 98
Heel mark resistance	Excellent
Leveling	Outstanding
pH	8.2 - 8.9
Powdering resistance	Excellent
Free styrene content.....	0.0
Shelf life.....	1 year

Directions For Use

Read the entire label before using this product.

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces. RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures and humidity may extend dry time. Initial application of 4 - 5 coats is recommended. **Note: This product is a self sealing finish, however, if tile is old, worn or porous, initially applying 1 - 2 coats of a sealer will enhance gloss and long term performance.** ROUTINE MAINTENANCE: Sweep large debris and dust mop (using a water based treatment). Damp mop or automatic scrub using a neutral pH cleaner. Buff or burnish the floor as desired. The use of a cleaner/restorer is recommended to condition the floor and extend the time between top scrub and recoating. INTERIM MAINTENANCE: Sweep large debris and dust mop (using a water-based treatment). Top scrub the floor using a top scrub cleaner and recommended floor pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 2 - 3 coats of finish as directed above. **Note: Slip resistance meets or exceeds (ASTM D 2047-04) James Machine 0.5 minimum.**



Safety

Keep out of reach of children. For institutional and commercial use. **CAUTION: MAY CAUSE EYE AND SKIN IRRITATION.** Contains Glycol Ether. Avoid contact with skin and eyes. Harmful if swallowed. **FIRST AID:** If splashed on skin or in eyes, flush with large quantities of water. If irritation persists, get medical attention. If swallowed, do not induce vomiting. Wash out mouth. Call a physician.

Available In

- Case/4 - 1 Gallon (3.78 L): Item #63204-00
- BIB/5 Gallons (18.9 L): Item #63239-00
- Pail/5 Gallons (18.9 L): Item #63205-00
- Drum/55 Gallon (208 L): Item #63255-00

Literature Item #63292-92

