

High Mileage®

Floor Finish



A floor finish that delivers excellent gloss build and outstanding durability for your floors, even in the heaviest of traffic.

Less Recoat Cycles = Labor Savings

- ▶ Extended recoat and stripping cycles yield labor savings and overall improved productivity
- ▶ Install up to five coats in one night

High Performance and Durability

- ▶ Specially designed higher solids formula builds durability over time
- ▶ Extremely tough in high traffic areas and resists dirt, black heel marks and scratches exceptionally well
- ▶ Unsurpassed buff response with all types of UHS equipment—propane, battery or cord electric

Designed For

- ▶ Healthcare
 - ▶ Education
 - ▶ Retail
 - ▶ BSC
 - ▶ Government
-



Use Overview

High Mileage® Floor Finish is a high solids, lower odor, ultra high speed floor finish for low to medium frequency locations floors. It is designed for use on all resilient floors.

- ▶ Blockade areas to be stripped or finished. Floors will be very slippery until dry.
- ▶ Strip floors, using a Diversey stripper per the instructions on the stripper label.

Coating

- ▶ Apply 3 or more medium coats using a clean finish mop or the Diversey ProSpeed™/MC or TrailBlazer™/MC Floor Finish Applicator System. Apply additional coats until desired gloss is obtained.
- ▶ Allow 30–45 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before burnishing.

Maintenance

- ▶ Dust mop or sweep. Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to label directions.
- ▶ If desired, dry buff using medium to aggressive pad and 1000–1500 rpm equipment. Ultra-high speed burnish using a medium aggressiveness pad and 2000+ rpm equipment.



Recoating

- ▶ Dust mop or sweep.
- ▶ Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to label directions.
- ▶ Blockade area and apply 1–2 uniform coats of finish using a clean mop. Allow finish to cure for 24 hours before burnishing.

Removal

- ▶ Remove using recommended Diversey brand stripper following label directions.

Precautions

- ▶ Do not dilute. Do not use on surfaces colder than 50° F (10° C). To avoid contamination, do not return unused finish to original container. Do not freeze.

Product Specifications

Description	
Color/Form	Milky white liquid
Flash Point	> 200° F (> 93.3° C)
pH	8.3
Scent	Mild
Slip Resistance	0.5 minimum (ASTM D2047)
Solubility	Complete
Specific Gravity	1.033

Hazard Rating

HMIS		NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

Available Items

Product Code	Description/Package Size	Dilution
5104811	1 x 5 gallon / 18.9 L Envirobox™/MC (TrailBlazer™/MC ready)	Ready-To-Use
5109638	6 x 2.64 Qt. / 2.5 L ProSpeed™/MC BIB (Bag-in-Box)	Ready-To-Use

Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at www.diversey.com or by calling 888 352 2249.