

# Bravo® 1500+

## UHS Floor Stripper

**New  
Improved  
Formula**



---

**Specially formulated to effectively and consistently remove the routine build-up of toughened finishes.**

### Powerful

- ▶ New formulation with improved stripping performance
- ▶ Quickly penetrates and emulsifies floor finish

### Reduces Labor

- ▶ Strips the accumulation of finish that normally accompanies high and ultra high speed floor care programs
- ▶ Powerful action requires less labor to strip floor

### Improved Formula

- ▶ Less time required to empty pickup tanks
- ▶ Easy pick-up with mop, wet vac or autoscrubber
- ▶ Eye and hand protection is not required at specified use dilution
- ▶ Concentrate not regulated as hazardous waste for disposal under EPA Resource Conservation and Recovery Act (RCRA) or Environment Canada regulations

---

### Designed For

- ▶ Education
  - ▶ Government
  - ▶ BSC
  - ▶ Retail
- 



# Use Overview

**Bravo® 1500+ UHS Floor Stripper** is specially formulated for high and ultra high speed floor care programs. It is recommended for use on resilient and non-resilient floors except unsealed wood, linoleum, cork and painted surfaces. Do not use on wood floors or painted surfaces. Test for softening or color bleeding on linoleum, rubber or asphalt floors. Use in well-ventilated areas.

- ▶ Use appropriate personal protective equipment.
- ▶ Dilute product as follows:
  - Light Build-up of Floor Finishes:** Dilute product between 1:8 (16 fl. oz./gal) with cold water.
  - Heavy Build-up of Floor Finishes:** Dilute product between 1:4 (32 fl. oz./gal) and 1:6 (24 fl. oz./gal) with cold water.
- ▶ Blockade areas to be stripped. Floors will become very slippery when stripper is applied. **Exercise Caution.**
- ▶ Apply liberal amounts of solution to uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with clean rag dampened with water.
- ▶ Let stripper solution soak in for 5-10 minutes. Mop agitate to loosen finish or sealer. Re-wet as necessary, do not allow stripper to dry on floor. Longer soak times may be necessary in cases of extreme build up.
- ▶ Hand or machine scrub thoroughly using black pads or stripping brushes.
- ▶ Pick-up all of the solution with a clean mop, wet vac, or an automatic scrubber. Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry.
- ▶ Thoroughly rinse floor with clear water.
- ▶ Let floor completely dry before applying recommended Diversey brand floor sealer or finish.



**Bravo® 1500+ UHS Floor Stripper** meets the newest and most stringent VOC standards in North America, including those adopted by the California Air Resources Board (CARB).

## Product Specifications

Description	Concentrate
<b>Dilution</b>	1:4-1:6 (Heavy Build-Up) 1:8 (Light/Medium Build-Up)
<b>pH</b>	12.1 (Concentrate) 11.4 (Use dilution 1:4)
<b>Scent</b>	Solvent
<b>Shelf Life</b>	2 years
<b>Specific Gravity</b>	1.016
<b>VOC</b>	Meets current California Air Resources (CARB) regulations

## Available Items

Product Code	Description/Package Size	Dilution
5594995	1 x 5 gallon / 18.9 L Envirobox™/MC	1:4-1:6, 1:8

## Hazard Rating

HMIS	Concentrate	NFPA	HMIS	Use Dilution 1:4	NFPA
3	Health	3	1	Health	1
0	Flammability	0	0	Flammability	0
0	Reactivity	0	0	Reactivity	0

4=Very High; 3=High; 2=Moderate; 1=Slight; 0=Insignificant.

## Safety Reminder

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at [www.diversey.com](http://www.diversey.com) or by calling 888 352 2249.