

# Pro Strip™ PURE Non-Corrosive Floor Stripper





A revolutionary floor finish stripper that does not require the user to wear personal protective equipment.

# **Breakthrough Formulation**

- ▶ Concentrate is non-corrosive to eyes and skin
- ▶ Reduces PPE requirements
- Concentrate not regulated as hazardous waste for disposal under EPA Resource Conservation and Recovery Act (RCRA) regulations
- DOT hazard classification CC-ORM-D

#### **Effective**

- ▶ Emulsifies floor finish for easy removal
- Removes conventional and ultra high speed finishes
- Low foam formula allows for easy pickup with mop, wet vac or autoscrubber

#### **Low Odor**

- Not formulated with butyl or ammonia
- Suitable for facilities where odor is a concern

# **Designed For**

- Food Service
- Education
- Healthcare
- Government
- BSC
- Retail
- Lodging



# **Use Overview**

**Pro Strip<sup>TM</sup> PURE Non-Corrosive Floor Stripper** is non-corrosive to eyes and skin without sacrificing performance. Chemical goggles and gloves are not required when used as directed. The highly effective formula quickly penetrates and emulsifies finish. Specially formulated for conventional and ultra high speed floor care programs.

#### **Use Directions**

- Blockade areas to be stripped. Floors will be very slippery until dry. Exercise caution. Wear chemical resistant footwear.
- For light build-up of finish use at a dilution of 1:6 (20 oz. to 1 gallon / 590 mL to 3.78 L). For heavy build-up of floor finish use at a dilution of 1:4 (32 oz. to 1 gallon).
- Apply liberal amounts of solution uniformly to floor with a mop. Start with the edges to give them more soak time. If splashing occurs, wipe off surfaces with a clean rag dampened with water.
- Let stripper solution soak for 7-10 minutes. Re-wet as necessary, do not allow solution to dry on floor. Longer soak times may be necessary in cases of extreme build-up.
- Hand or machine scrub thoroughly using appropriate stripping pads or stripping brush.
- Pick-up all of the solution with a clean mop, wet vac or automatic scrubber. Mop up any "tracks" left by wet vacs or automatic scrubbers before they dry.
- ▶ Thoroughly rinse floor with clear water.
- Let floor dry completely before applying recommended Diversey brand floor sealer or finish.



**IMPORTANT:** Do not use on wood floors or painted surfaces, as this product may harm these surfaces. Test for softening or color bleeding on linoleum, rubber or asphalt floors before using.

Pro Strip™ PURE Non-Corrosive Floor Stripper meets the newest and most stringent VOC standards in North America, including those adopted by the California Air Resources Board (CARB).

# **Product Specifications**

Description	
Color/Form	Clear colorless liquid
Flash Point	> 200° F (> 93.4° C)
рН	11.5 (Concentrate) 11.0 (Dilution, 1:4)
Scent	Cherry Almond
Shelf Life	2 years
Solubility	Dispersible
Specific Gravity	1.06
VOC	Meets current California Air Resources (CARB) regulations

# **Available Items**

Product Code	Description/Package Size	Dilution
5594354	1 x 5 gallon / 18.9 L Envirobox <sup>TM/MC</sup>	1:4 (heavy build-up), 1:6 (light build-up)

## **Safety Reminder**

Please make sure your employees read and understand the product label and Material Safety Data Sheet before using this product. The label contains directions for use, and both the label and MSDS contain hazard warnings, precautionary statements and first aid procedures. MSDS are available on-line at www.diversey.com or by calling 888 352 2249.

## **Hazard Rating**

HMIS	Concentrate	NFPA
2	Health	2
0	Flammability	0
0	Reactivity	0

HMIS	Use Dilution 1:4	NFPA
1	Health	1
0	Flammability	0
0	Reactivity	0

 $4 = Very\,High; 3 = High; 2 = Moderate; 1 = Slight; 0 = Insignificant.$ 

