



Shineline Seal[®]

thermoplastic floor sealer

A popular option to condition, seal and protect, Shineline Seal is a 24% solids, thermoplastic sealer. It is compatible with all Spartan floor finishes.



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee, OH 43537
 1-800-537-8990
 www.spartanchemical.com

HIGH SOLIDS & ECONOMICAL:

Two coats of the high solids Shinline Seal conditions, seals and protects, laying a foundation for high gloss, wet look floors. Superior leveling, gives coverage rates up to 3000 square feet per gallon.

DURABLE:

Shinline Seal IS a flexible, tough seal, which helps prevent damage and deterioration due to abrasion, scratching, scuffing, and wear. Shinline Seal acts as the last line of defense to protect floors in cases of extreme traffic, making it ideal for programs seeking to reduce strip outs through scrub and recoats.

NON-YELLOWING:

Shinline Seal does not contain ingredients that will yellow, distort, diminish, or discolor surfaces.

VERSATILE:

Shinline Seal is an ideal foundation for all Spartan floor finishes. It is also compatible on a myriad of porous substrates, including resilient tile, concrete, terrazzo, marble and more.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

1. Completely strip the floor with a Spartan stripper.
2. Apply Shinline Seal with a floor finish mop or applicator. Wring out the mop until it no longer drips and apply Shinline Seal in a figure eight motion.
3. In ideal weather conditions, Shinline Seal should dry within 30 minutes. After it is dry to the touch, a second coat of Shinline Seal should be applied and allowed to dry completely.
4. Using a clean mop head, add 2 – 3 coats of Spartan finish.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Non-volatile Solids – 24%
 Specific Gravity - 1.025 – 1.030 @ 24°C/75°F
 pH (Concentrate) - 8.3 - 8.9
 Stability:
 a. Storage @ 24°C/75°F - One year minimum
 b. Accelerated @ 52°C/125°F - 30 days minimum
 c. Freeze/Thaw - Can withstand three cycles
 Static coefficient of friction meets or exceeds 0.5 as determined by the ASTM method D2047.

COVERAGE:

Up to 3,000 square feet per gallon depending on application method and porosity of floor.



Distributed by:

PACKAGING	
400465	330-gallon totes
400455	55-gallon drum
400430	30-gallon drum
400415	15-gallon drum
400405	5-gallon pail
400404	1-gallon (4 per case)



Label copy is provided in English, Spanish, and French. Secondary labels are also available.

GUARANTEE: Spartan's modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product Available Worldwide. For institutional and industrial use only.

© SCC 511 L4004